

CARTER OPEN GEAR



GREASE



TOTAL

Heavy Duty Open Gear Grease

APPLICATIONS

Multi-purpose open gear grease.

- **CARTER OPEN GEAR** grease is formulated to provide superior load-wear protection on all exposed gears.
- **CARTER OPEN GEAR** grease is highly adhesive. While many other open gear lubricants contain solvents requiring evaporation, **CARTER OPEN GEAR** grease is solvent free. Gears lubricated with this product are ready for immediate use.

ADVANTAGES

- Highly adhesive and tacky.
- Incorporates anti-wear and anti-corrosion additives.
- Excellent lubricity properties.
- Solvent free.
- Good mechanical and thermal stability.
- Moisture resistant.

TYPICAL CHARACTERISTICS	METHODS	CARTER OPEN GEAR
Appearance	Visual	Smooth Black & Tacky
Operating Range, °F		25 - 400
Thickener Type		Inorganic
NLGI Grade		2
Penetration Worked, 60xx	ASTM D 217	285 - 305
Dropping Point, °F	ASTM D 2265	None
Corrosion Prevention	ASTM D 1743	Pass
Timken OK Load, lbs.	ASTM D 2509	40
4 Ball Wear, 40kg, mm	ASTM D 2266	0.84
Base Oil Properties:		
Viscosity @ 210°F, SUS	ASTM D 445	3000
Flash Point, PM, °F	ASTM D 92	378

Revised 02/09 WHC

TOTAL Specialties USA, Inc.

Linden, NJ 07036
5 North Stiles Street
1-800-323-3198
www.totalspecialties.com

CARTER 6-2016

This lubricant must be applied as recommended and used for the application for which it was designed. TOTAL Specialties USA, Inc. will have no responsibility for any injury to persons or property resulting from misuse or misapplication of the lubricant. A safety data sheet conforming to the OSHA Hazard Communication Standard 29 CFR Section 1910.1200 can be downloaded at www.totalspecialties.com. Copyright 2016 All rights reserved.