


CLASSIC SN

SAE 20, 30, 40, 10W-40



Passenger car motor oil with API SN quality

APPLICATIONS

All types of service

- **CLASSIC SN OILS** are designed to meet lubrication requirements of today's naturally aspirated, turbo-charged and super-charged gasoline fueled engines.
- **CLASSIC SN OILS** are formulated to provide excellent oxidation stability and low temperature flow properties. The multi-grades 10W-40 (shown below) and 20W-50 (separate data sheet) are not fuel economy grades for passenger cars. All oil grades contain friction modifiers and may not be suitable for wet clutches in motorcycles.

PERFORMANCE

API SN

SUITABLE FOR:

GM, Ford, Chrysler, Dodge, Jeep, Honda, Acura, Toyota, Lexus, Mazda, Nissan, Infinity, Subaru, Hyundai, Kia, Suzuki, and Mitsubishi.

CUSTOMER BENEFITS

High technical performance

- **CLASSIC SN** automotive engine oils contain enhanced detergents, dispersants, anti-oxidants, anti-wear and corrosion prevention properties improve the fluid performance under all types of service.
- The multi-grade oils have higher viscosity than fuel economy grades and have enhanced low temperature flow properties ensuring easy cold starts. Engine components are lubricated quickly giving longer life.

CHARACTERISTICS

TYPICAL PROPERTIES--CLASSIC SN OILS					
SAE grade	20	30	40	50	10W-40
Density at 60 F ASTM D 1298	0.877	0.89	0.898	0.90	0.875
Viscosity, cSt @ 100°C ASTM D 445	7.5	10.5	14.5	17.5	14.5
Viscosity, cSt @ 40°C ASTM D 445	51	85	148	180	84
Cold Crank cp max ASTM D 5293	-	-	-	-	7000 @ -25C
Viscosity Index ASTM D 2270	113	104	98	100	180
Pour Point, °C ASTM D 97	-15	-12	-12	-12	-33
Total base number ASTM D 2896	7	7	7	7	7

TOTAL Specialties USA, Inc.

Linden, NJ 07036
5 North Stiles Street
1-800-323-3198
www.totalspecialties.com

CLASSIC

7-2016

This lubricant must be applied as recommended and used for the application for which it was designed. TOTAL Specialties USA, Inc. will have no responsibility for any injury to persons or property resulting from misuse or misapplication of the lubricant. A safety data sheet conforming to the OSHA Hazard Communication Standard 29 CFR Section 1910.1200 can be downloaded at www.totalspecialties.com. Copyright 2016 All rights reserved.