

NEVASTANE® CLEAR 15 & 68



FOOD INDUSTRY

TOTAL

USP White Mineral Oil for the Food and Pharmaceutical Industries.

APPLICATIONS

USP White Mineral Oil.

3H & H1 Registered Food Grade Oil.



- **NEVASTANE CLEAR 15 & 68** are made with USP white mineral oil, **NSF listed 3H and H1**. They are recommended for use as a release agent in food processing plants where there is direct contact with foodstuff, such as dough dividers. These products comply with **FDA 21 CFR 172.878** and **FDA 21 CFR 178.3620(a)**. The minimal amount possible should be used to achieve the desired technical effect on the equipment.
- **NEVASTANE CLEAR 15 & 68** oils are suitable for use on machinery used for producing, manufacturing, packing, preparing, and packaging food where there is a possibility of incidental food contact. These products should be used as recommended by a responsible company representative. Prolonged contact with the skin may cause mild irritation. See the Material Safety Data Sheet for additional information.
- **NSF 3H, H1 Registered meets USDA 1998 H1 Guidelines for incidental contact with food.**

ADVANTAGES

- Water white.
- Low and high temperature service.
- High temperature stability.
- 3H and H1 registered.
- Compatible with elastomers and seals.
- Good film strength.

TYPICAL CHARACTERISTICS	METHODS	NEVASTANE CLEAR	
		15	68
ISO VG Grade		15	68
NSF Registration Number		139922	140032
Appearance	Visual	Bright, Clear, Water White	
Viscosity @ 40°C, cSt	ASTM D 445	14.2-17.0	65.0-70.0
Saybolt Color, min.		30	30
Flash Point, COC, °F(°C)	ASTM D 92	350(178)	450(234)
Pour Point, °F(°C)	ASTM D 97	10(-12)	10(-12)
Density @ 60°F, lbs./gal.	ASTM D 1298	7.17	7.26
Specific Gravity @ 60°F/60°F	ASTM D 1298	0.859	0.863

TOTAL Specialties USA, Inc.

Linden, NJ 07036
5 North Stiles Street
1-800-323-3198
www.totalspecialties.com

NEVASTANE 7-2016

This lubricant must be applied as recommended and used for the application for which it was designed. TOTAL Specialties USA, Inc. will have no responsibility for any injury to persons or property resulting from misuse or misapplication of the lubricant. A safety data sheet conforming to the OSHA Hazard Communication Standard 29 CFR Section 1910.1200 can be downloaded at www.totalspecialties.com. Copyright 2016 All rights reserved.