

OSYRIS 302 S



METALWORKING



TOTAL

Hot Melt Rust Preventative.

APPLICATIONS

- **OSYRIS 302 S** is a translucent, grease-like material that provides excellent rust protection under a variety of conditions, including outdoor storage. Although this material is soft, it retains considerable rust preventative properties during handling because of its ability to repair itself.
- **OSYRIS 302 S** is non-staining, low odor, and can be applied by conventional brush, dip, or spray methods.

ADVANTAGES

- Ability to repair itself during handling.
- Outstanding oxidation resistance.
- Non-staining.

TYPICAL CHARACTERISTICS	OSYRIS 302 S
	Appearance
Color, ASTM D-1500	3.0
Odor	Mild Petroleum
Viscosity at 40°C, cSt	7.1 - 10.0
Density @ 60 °F, lbs./gal.	7.26
Specific Gravity @ 60/60 °F	0.871
Flash Point, COC, °F	370
Copper Strip Corrosion	1A-1B
Lubricity Content, %	61.0
Film Type	Grease
Indoor Protection, months	12+
Outdoor Protection, months	5 - 6
Congealing Point, °F, ASTM D-938	95 - 105

TOTAL Specialties USA, Inc.

Linden, NJ 07036
5 North Stiles Street
1-800-323-3198
www.totalspecialties.com

OSYRIS 6-2016

This lubricant must be applied as recommended and used for the application for which it was designed. TOTAL Specialties USA, Inc. will have no responsibility for any injury to persons or property resulting from misuse or misapplication of the lubricant. A safety data sheet conforming to the OSHA Hazard Communication Standard 29 CFR Section 1910.1200 can be downloaded at www.totalspecialties.com. Copyright 2016 All rights reserved.