

# VESTAN FM GREASE



FOOD INDUSTRY



**TOTAL**

**Multi-Purpose, Aluminum Complex, Food Grade Grease.**

## APPLICATIONS

Food service, food packaging, and food preparation industries.

- **VESTAN FM GREASE** contains an aluminum complex thickener and additives to improve performance. The thickener improves water resistance and high temperature shear stability while rust inhibitors and antioxidants enhance performance in wet and hot environments. This product is an extreme pressure (EP), food grade grease designed for lubricating food processing equipment. It is permitted for use in federally inspected meat and poultry plants where there is a potential for incidental contact with food products.
- **VESTAN FM GREASE** is recommended for applications where incidental contact with food or food packaging can occur such as the lubrication of heavily loaded, high output machinery. It may be applied either manually or automatically via a central system.

## SPECIFICATIONS

- ISO 6743-9: L-XBEHB-2
- DIN 51502: KPF2P-20
- NSF H1 Registered

## ADVANTAGES

Water resistant.

- Strong adhesion to surfaces.
- Excellent water wash off resistance.
- Good extreme pressure (EP) protection.
- Resists shock loading impacts.
- Very good corrosion and oxidation protection.
- Extends re-greasing intervals.

TYPICAL CHARACTERISTICS	METHODS	VESTAN FM GREASE
NLGI Grade		<b>2</b>
Appearance	Visual	White, slightly tacky
Thickener Type		Aluminum Complex
Penetration Worked, 60x	ASTM D 217	280
Dropping Point, °F(°C)	ASTM D 2265	480(249)
Timken OK Load, lbs.	ASTM D 2509	40
4-Ball EP, Weld Load, kg	ASTM D 2596	250
Base oil Viscosity @ 40°C, cSt	ASTM D 445	116
Estimated Operating Range, °F		-10 to 350

**TOTAL Specialties USA, Inc.**

Linden, NJ 07036  
5 North Stiles Street  
1-800-323-3198  
www.totalspecialties.com

VESTAN 6-2016

This lubricant must be applied as recommended and used for the application for which it was designed. TOTAL Specialties USA, Inc. will have no responsibility for any injury to persons or property resulting from misuse or misapplication of the lubricant. A safety data sheet conforming to the OSHA Hazard Communication Standard 29 CFR Section 1910.1200 can be downloaded at [www.totalspecialties.com](http://www.totalspecialties.com). Copyright 2016 All rights reserved.