

# FLUIDMATIC CVT MV



TOTAL

## Specialty ATF for Continuously Variable Transmissions

### APPLICATIONS

#### Types of service

- **FLUIDMATIC CVT MV** is recommended as a multi-vehicle ATF for continuously variable transmissions (CVT), especially when chain or belt drives are used.
- Consult your owner's manual and our suitability guide regarding your recommended CVT fluid.

### PERFORMANCE

#### Specifications

This product carries no OEM approvals but is suitable for use in many belt driven CVT applications. Please see next page for suitable for use listing.

### CUSTOMER BENEFITS

#### High technical performance

- Exceptional cleanliness of delicate control valves resulting in trouble-free transmission performance.
- High viscosity index gives excellent performance over a wide temperature range. Fluid stays in grade.
- Special frictional properties provide the required shift feel characteristics.
- Excellent anti-wear, anti-corrosion, anti-foam and oxidation resistance.
- Excellent low temperature fluidity protects against wear under extremely cold operating conditions.

### CHARACTERISTICS

PROPERTY	Test Method	FLUIDMATIC CVT MV
Color	Visual	Red
API Gravity (lb/gal)		35 (7.07)
Viscosity, cP @ -40°C (-40°F)	ASTM D-2983	23,400
Viscosity, cSt @ 100°C:	ASTM D-445	7.6
Viscosity Index	ASTM D-2270	180
Pour Point, °C (°F)	ASTM D-97	-51 (-59)
Flash Point, °C (°F)	ASTM D-93	190 (374)

**TOTAL Lubricants USA, Inc.**

**Fluidmatic CVT MV**  
Sheet issued 4-29-2013:

5 North Stiles Street  
Linden, NJ 07036  
908.862.9300 or 800.323.3198  
www.totallubricantsusa.com

TOTAL Lubricants USA with a policy of continuous improvement, reserves the right to change specifications as our technology progresses.  
We are not responsible for the misuse and/or misapplication of our products. MSDS are found on our web sites.

# FLUIDMATIC CVT MV



## Specialty ATF for Continuously Variable Transmissions

### RECOMMENDED FOR:

Audi/VW TL 52180,  
G 052 180 (CVT)  
G 052 516 (CVT)  
**BMW CVT (83 22 0 136 376, 83 22 0 429 154)**  
Chrysler/Dodge/Jeep (NS-2, CVTF+4)  
Daihatsu—see Toyota  
Esso CVT EZL 799 (VTF) **83 22 0 136 376**  
Ford CVT 30/ Mercon C  
Ford CVT23  
**Ford CVT WSS-M2C-933-A (XT-7QCFT)**  
GM Saturn (DEX-CVT)  
Honda Genuine CVT, (HMMF)  
Hyundai/Kia SP-CVT 1  
Jeep (see Chrysler)  
Mazda—see Toyota  
Mercedes Benz (236.20)  
Mercedes Benz CVT 28  
Mercon C  
Mini Cooper EZL 799  
Mitsubishi CVTF-J1  
Mopar® CVT+4 (VTF) # 05191184AA  
Motorcraft® # XT-7-QCFT (VTF) (CVT);  
Multimatic Fluid HMMF  
Nissan CVT NS-1, NS-2;  
Punch EZL 799A  
Saturn Dexron® CVT,  
Suzuki CVT Green 1, (TC, NS-2)  
Shell GREEN 1V;  
Subaru (Lineartronic CVTF)  
Suzuki NS-2/TC, CVT Green 1  
Toyota/Mazda/Daihatsu CVT Fluid TC  
VW –see Audi

### NOT SUITABLE:

**Audi:** G 055 005 A2 (CVT); G 052 180 A2 (CVT); G 052 516 A2 (CVT);  
**Ford** hybrid CVT units  
**Fujjyuuko** I-CVTF FG  
**Toyota** hybrid CVT units  
**Volvo** CVT 4959

**TOTAL Lubricants USA, Inc.**

**Fluidmatic CVT MV**  
Sheet issued 4-29-2013:

5 North Stiles Street  
Linden, NJ 07036  
908.862.9300 or 800.323.3198  
[www.totallubricantsusa.com](http://www.totallubricantsusa.com)