



SAFETY DATA SHEET

According to the Hazard Communication Standard, 29 CFR 1910.1200

SDS # : 083334

CIRKAN RO 150

Date of the previous version: not applicable

Revision Date: 2015-04-17

Version 1

1. IDENTIFICATION

Product identifier

Product name CIRKAN RO 150

Other means of identification

Product Code(s) 083334

Number 13L
Substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Identified uses Circulating oil. Machine oil.

Uses advised against Do not use for any purpose other than the one for which it is intended

Details of the supplier of the safety data sheet

Supplier Address TOTAL Specialties USA Inc
1201 Louisiana Street, Suite 1800
Houston, TX 77002
Phone: +1 800 323 3198

Contact Point Technical/ HSEQ

E-mail Address USRMLIN-info@total.com

Emergency telephone number

Company Phone Number +1 (908) 862-9300
Emergency telephone CHEMTREC: +1 800 424 9300 (24h)

2. HAZARDS IDENTIFICATION

Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Label elements

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Version GNAM



SDS # : 083334

CIRKAN RO 150

Date of the previous version: not applicable

Revision Date: 2015-04-17

Version 1

Unknown Acute Toxicity

No information available

Hazards not otherwise classified (HNOC)

- May be harmful if inhaled

Other information

- Should not be released into the environment

3. COMPOSITION/INFORMATION ON INGREDIENTS

This material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). The product contains no substances which at their given concentration, are considered to be hazardous to health.

Additional information

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

4. FIRST AID MEASURES

First aid measures for different exposure routes

General advice	IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.
Eye contact	Rinse thoroughly with plenty of water, also under the eyelids. Rinse immediately with plenty of water and seek medical advice. Keep eye wide open while rinsing.
Skin contact	Remove contaminated clothing and shoes. Wash off with soap and water. Wash contaminated clothing before reuse.
Inhalation	Move to fresh air.
Ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately. If swallowed, do not induce vomiting - seek medical advice.

Most important symptoms/effects, acute and delayed

Skin contact	Not classified.
Eye contact	Not classified.
Inhalation	May be harmful if inhaled. Inhalation of vapors in high concentration may cause irritation of respiratory system.
Ingestion	Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Version GNAM



SDS # : 083334

CIRKAN RO 150

Date of the previous version: not applicable

Revision Date: 2015-04-17

Version 1

Symptoms Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Foam. Carbon dioxide (CO₂). ABC powder. Water spray or fog.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

Special Hazard Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration.

Hazardous Combustion Products Hazardous decomposition products due to incomplete combustion. Carbon monoxide.

Explosion Data

Sensitivity to Mechanical Impact none.

Sensitivity to Static Discharge none.

Protective Equipment and Precautions for Firefighters As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Evacuate non-essential personnel.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

General Information Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. Remove all sources of ignition.

Other information See Section 12 for additional information.

Environmental precautions

General Information Do not allow material to contaminate ground water system. Try to prevent the material from entering drains or water courses. Local authorities should be advised if significant spillages cannot be contained. See Section 12 for additional Ecological Information.

Methods and materials for containment and cleaning up

Methods for cleaning up Dam up. Keep in suitable, closed containers for disposal. Soak up with inert absorbent material. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use mechanical means such as pumps, skimmers and absorbent materials.

7. HANDLING AND STORAGE

Version GNAM



SDS # : 083334

CIRKAN RO 150

Date of the previous version: not applicable

Revision Date: 2015-04-17

Version 1

Precautions for safe handling

Advice on safe handling

When using, do not eat, drink or smoke. For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing.

Prevention of fire and explosion

Take precautionary measures against static discharges: Ground/bond containers, tanks and transfer/receiving equipment.

Hygiene measures

Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets. When using, do not eat, drink or smoke. Use personal protective equipment as required. Wash hands before breaks and at the end of workday. Wash hands with water as a precaution. Avoid breathing vapors, mist or gas.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions

Keep away from food, drink and animal feedingstuffs. Keep in a bunded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Protect from frost, heat and sunlight. Protect from moisture.

Materials to Avoid

Strong oxidizing agents. Strong acids. Strong bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits

Mineral oil mist:
USA: OSHA (PEL) TWA 5 mg/m³, NIOSH (REL) TWA 5 mg/m³, STEL 10 mg/m³, ACGIH (TLV) TWA 5 mg/m³ (highly refined).

Exposure controls

Engineering Measures

Apply technical measures to comply with the occupational exposure limits. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.

Individual protection measures, such as personal protective equipment

Version GNAM



SDS # : 083334

CIRKAN RO 150

Date of the previous version: not applicable

Revision Date: 2015-04-17

Version 1

General Information	If the product is used in mixtures, it is recommended that you contact the appropriate protective equipment suppliers. These recommendations apply to the product as supplied.
Eye/Face Protection	If splashes are likely to occur, wear: Safety glasses with side-shields.
Skin and body protection	Wear suitable protective clothing. Protective shoes or boots. Long sleeved clothing.
Hand Protection	Hydrocarbon-proof gloves. Nitrile rubber. Neoprene gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
Hygiene measures	Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets. When using, do not eat, drink or smoke. Use personal protective equipment as required. Wash hands before breaks and at the end of workday. Wash hands with water as a precaution. Avoid breathing vapors, mist or gas.

9. PHYSICAL AND CHEMICAL PROPERTIES**Physical and chemical properties**

Color	amber
Physical State @20°C	liquid
Odor	Petroleum distillates
Odor Threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
pH		Not applicable	
Melting point/range		No information available	
Boiling point/boiling range		Not applicable	
Flash point	227 °C		Cleveland Open Cup (COC)
	440 °F		ASTM D 92
			Cleveland Open Cup (COC).
			ASTM D 92.
Evaporation rate		No information available	
Flammability Limits in Air upper	-	No information available	
		No information available	

Version GNAM



SDS # : 083334

CIRKAN RO 150

Date of the previous version: not applicable

Revision Date: 2015-04-17

Version 1

Lower	-	No information available	
Vapor Pressure		No information available	
Vapor density		No information available	
Relative density	0.884	@ 15 °C	
Density	884 kg/m ³	@ 15 °C	
Water solubility		Not applicable	
Solubility in other solvents		No information available	
logPow		No information available	
Autoignition temperature		No information available	
Decomposition temperature		No information available	
Viscosity, kinematic	150 mm ² /s	@ 40 °C	ASTM D 2270
Explosive properties	Not explosive		
Oxidizing Properties	Not applicable		
Possibility of hazardous reactions	Not applicable		
<u>Other information</u>			
Specific Gravity	0.884	@ 15 °C	
Freezing Point		No information available	
Pour point	-15 °C		ASTM D 97

10. STABILITY AND REACTIVITY

<u>Reactivity</u>	No information available.
<u>Chemical stability</u>	Stable under recommended storage conditions.
<u>Possibility of hazardous reactions</u>	None under normal processing.
<u>Conditions to Avoid</u>	Heat (temperatures above flash point), sparks, ignition points, flames, static electricity. Heat, flames and sparks. Take precautionary measures against static discharges.
<u>Incompatible Materials</u>	Strong oxidizing agents. Strong acids. Strong bases.
<u>Hazardous Decomposition Products</u>	Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot.

11. TOXICOLOGICAL INFORMATION**Acute toxicity****Information on likely routes of exposure****Product Information**

Skin contact	Not classified.
Eye contact	Not classified.

Version GNAM



SDS # : 083334

CIRKAN RO 150

Date of the previous version: not applicable

Revision Date: 2015-04-17

Version 1

Inhalation	May be harmful if inhaled. Inhalation of vapors in high concentration may cause irritation of respiratory system.
Ingestion	Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Numerical measures of toxicity - Product Information

ATEmix (oral)	5027 mg/kg
ATEmix (dermal)	5027 mg/kg
Inhalation	
ATEmix (inhalation-dust/mist)	5.1 mg/l
ATEmix (inhalation-vapor)	20.2 mg/l

Information on toxicological effects

Symptoms Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization Not classified as a sensitizer.
Carcinogenicity This product is not classified carcinogenic.

Mutagenicity This product is not classified as mutagenic.
Reproductive toxicity This product does not present any known or suspected reproductive hazards.
Aspiration Hazard Not classified.

12. ECOLOGICAL INFORMATION**Ecotoxicity****Acute aquatic toxicity - Product Information**

No experimental data available

Acute aquatic toxicity - Component Information

No information available

Chronic aquatic toxicity - Product Information

No experimental data available

Chronic aquatic toxicity - Component Information

No information available

Version GNAM



SDS # : 083334

CIRKAN RO 150

Date of the previous version: not applicable

Revision Date: 2015-04-17

Version 1

Effects on terrestrial organisms No experimental data available .

Persistence and degradability

General Information No information available.

Bioaccumulative potential

Product Information No information available.

logPow No information available

Component Information No information available.

Mobility

Soil Given its physical and chemical characteristics, the product generally shows low soil mobility

Air Loss by evaporation is limited

Water The product is insoluble and floats on water

Other adverse effects

General Information No information available

13. DISPOSAL CONSIDERATIONS**Waste treatment**

Waste Disposal Methods Dispose of in accordance with local regulations.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

This product contains one or more substances that are listed with the State of California as a hazardous waste.

14. TRANSPORT INFORMATION

DOT Not regulated

TDG Not regulated

MEX Not regulated

ICAO/IATA Not regulated

Version GNAM



SDS # : 083334

CIRKAN RO 150

Date of the previous version: not applicable

Revision Date: 2015-04-17

Version 1

IMDG/IMO Not regulatedADR/RID Not regulatedADN Not regulated**15. REGULATORY INFORMATION**

International Inventories All the substances contained in this product are listed or exempted from listing in the following inventories:
U.S.A. (TSCA)

U.S. Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard	no
Chronic Health Hazard	no
Fire Hazard	no
Sudden Release of Pressure Hazard	no
Reactive Hazard	no

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations**California Proposition 65**

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Paraffin oils (petroleum), catalytic dewaxed heavy 64742-70-7	X				

Version GNAM



SDS # : 083334

CIRKAN RO 150

Date of the previous version: not applicable

Revision Date: 2015-04-17

Version 1

Distillates (petroleum), hydrotreated light paraffinic 64742-55-8	X				
---	---	--	--	--	--

16. OTHER INFORMATION

NFPA	Health Hazard 1	Flammability 1	Instability 0	Physical and chemical hazards -
HMIS	Health Hazard 1	Flammability 1	Physical Hazard 0	Personal protection X

NFPA (National Fire Protection Association)

HMIS (Hazardous Material Information System)

Hazards are split into categories each with a 0 to 4 rating, 0 meaning no hazard and 4 meaning high hazard

Revision Date: 2015-04-17
Revision Note No information available
Abbreviations, acronyms

Legend

Section 8
 ACGIH - American Conference of Governmental Industrial Hygienists
 OSHA - Occupational Safety and Health Administration
 NIOSH - National Institute for Occupational Safety and Health
 TLV - Threshold Limit Values
 PEL - Permissible Exposure Limits
 IDHL - Immediately Dangerous to Life or Health concentrations
 TWA - Time Weight Average
 STEL - Short Term Exposure Limits
 S* - Skin notation
 TSCA - Toxic Substance Control Act

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of the safety data sheet

Version GNAM