



SAFETY DATA SHEET

According to the Hazard Communication Standard, 29 CFR 1910.1200

SDS # : 084009

TRANS. MDL NA 85W-140

Date of the previous version: 2015-09-21

Revision Date: 2015-10-13

Version 4.02

1. IDENTIFICATION

Product identifier

Product name TRANS. MDL NA 85W-140

Other means of identification

Product Code(s) 084009

Number 5YP
Substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Identified uses Gear oil. Transmission fluid.

Uses advised against Do not use for any purpose other than the one for which it is intended

Details of the supplier of the safety data sheet

Supplier Address TOTAL Specialties USA Inc
1201 Louisiana Street, Suite 1800
Houston, TX 77002
Phone: +1 800 323 3198

Contact Point Technical/ HSEQ

E-mail Address USRMLIN-info@total.com

Emergency telephone number

Company Phone Number

+1 (908) 862-9300

Emergency telephone

CHEMTREC: +1 800 424 9300 (24h)

2. HAZARDS IDENTIFICATION

Classification

Serious eye damage/eye irritation - Category 2B

Label elements

WARNING

Causes eye irritation

Version GNAM



SDS # : 084009

TRANS. MDL NA 85W-140

Date of the previous version: 2015-09-21

Revision Date: 2015-10-13

Version 4.02

Precautionary Statements - Prevention

Wash hands and face thoroughly after handling

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention

Unknown Acute Toxicity

Not applicable

Hazards not otherwise classified (HNOC)

None known

Other information

Physical-Chemical Properties Contaminated surfaces will be extremely slippery.

Environmental properties Should not be released into the environment.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %
phosphoric acid esters, amine salts	^	1 - 5
1-Propene,2-Methyl-,sulfurized	68511-50-2	1-5

** The exact percentage (concentration) of composition has been withheld as a trade secret*

4. FIRST AID MEASURES**First aid measures for different exposure routes****General advice**

IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE. Take off contaminated clothing and shoes immediately. Do not get in eyes, on skin, or on clothing.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, consult a specialist. Check for and remove any contact lenses. Rinse immediately with plenty of water and seek medical advice.

Skin contact

Remove contaminated clothing and shoes. Wash off with soap and water. Wash contaminated clothing before reuse. Wash off immediately with plenty of water for at least 15 minutes.

Inhalation

Move to fresh air. Inhalation of high concentrations of vapor or aerosols may cause irritation of the upper respiratory tract.

Version GNAM



SDS # : 084009

TRANS. MDL NA 85W-140

Date of the previous version: 2015-09-21

Revision Date: 2015-10-13

Version 4.02

Ingestion If swallowed, do not induce vomiting - seek medical advice. Rinse mouth. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Remove from exposure, lie down.

Most important symptoms/effects, acute and delayed

Skin contact Causes mild skin irritation. Prolonged contact may cause redness and irritation.

Eye contact Causes eye irritation.

Inhalation Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.

Ingestion Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Itching.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Foam. Carbon dioxide (CO₂). Water spray. Dry powder. ABC powder.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

Special Hazard Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration.

Explosion Data

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective Equipment and Precautions for Firefighters As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Evacuate non-essential personnel.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

General Information Ensure adequate ventilation. For personal protection see section 8. Keep non-involved personnel away from the area of spillage. Do not touch or walk through spilled material. Avoid breathing vapors or mists. Contaminated surfaces will be extremely slippery.

Other information See Section 12 for additional information.

Environmental precautions

Version GNAM



SDS # : 084009

TRANS. MDL NA 85W-140

Date of the previous version: 2015-09-21

Revision Date: 2015-10-13

Version 4.02

General Information

Prevent further leakage or spillage if safe to do so. Prevent entry into waterways, sewers, basements or confined areas. Local authorities should be advised if significant spillages cannot be contained. Do not allow material to contaminate ground water system. Try to prevent the material from entering drains or water courses.

Methods and materials for containment and cleaning up

Methods for cleaning up

Keep in suitable, closed containers for disposal. Dam up. Soak up with inert absorbent material. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

When using, do not eat, drink or smoke. For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing.

Prevention of fire and explosion

Take precautionary measures against static discharges: Ground/bond containers, tanks and transfer/receiving equipment.

Hygiene measures

Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. Wash hands and face before breaks and immediately after handling the product. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets. When using, do not eat, drink or smoke. Use personal protective equipment as required. Wash hands before breaks and at the end of workday. Avoid breathing vapors, mist or gas. Avoid prolonged and repeated contact with the skin, especially with used or waste product. Regular cleaning of equipment, work area and clothing is recommended.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions

Keep away from food, drink and animal feedingstuffs. Keep in a banded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Protect from frost, heat and sunlight. Protect from moisture. Keep in properly labeled containers.

Materials to Avoid

Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Version GNAM



SDS # : 084009

TRANS. MDL NA 85W-140

Date of the previous version: 2015-09-21

Revision Date: 2015-10-13

Version 4.02

Exposure limits

Mineral oil mist:
USA: OSHA (PEL) TWA 5 mg/m³, NIOSH (REL) TWA 5 mg/m³, STEL 10 mg/m³, ACGIH (TLV) TWA 5 mg/m³ (highly refined).

Exposure controls

Engineering Measures

Apply technical measures to comply with the occupational exposure limits. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.

Individual protection measures, such as personal protective equipment

General Information

Protective engineering solutions should be implemented and in use before personal protective equipment is considered.

Eye/Face Protection

If splashes are likely to occur, wear: Safety glasses with side-shields.

Skin and body protection

Wear suitable protective clothing. Protective shoes or boots. Long sleeved clothing.

Hand Protection

Hydrocarbon-proof gloves. Fluorinated rubber. Nitrile rubber. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Respiratory protection

None required under normal usage. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures

Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. Wash hands and face before breaks and immediately after handling the product. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets. When using, do not eat, drink or smoke. Use personal protective equipment as required. Wash hands before breaks and at the end of workday. Avoid breathing vapors, mist or gas. Avoid prolonged and repeated contact with the skin, especially with used or waste product. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Version GNAM



SDS # : 084009

TRANS. MDL NA 85W-140

Date of the previous version: 2015-09-21

Revision Date: 2015-10-13

Version 4.02

Color amber
 Physical State @20°C liquid
 Odor Hydrocarbon-like
 Odor Threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
pH		Not applicable	
Melting point/range		No information available	
Boiling point/boiling range		Not applicable	
Flash point	210 - 300 °C 435 - 572 °F		ASTM D 93 ASTM D 93.
Evaporation rate		No information available	
Flammability Limits in Air		No information available	
upper	-	No information available	
Lower	-	No information available	
Vapor Pressure		No information available	
Vapor density		No information available	
Relative density	0.855 - 0.905	@ 15 °C	
Density	855 - 905 kg/m ³	@ 15 °C	
Water solubility		Insoluble	
Solubility in other solvents		No information available	
logPow		No information available	
Autoignition temperature		Not applicable	
Decomposition temperature		No information available	
Viscosity, kinematic	353 mm ² /s	@ 40 °C	ASTM D 445
Explosive properties	Not explosive		
Oxidizing Properties	Not applicable		
Possibility of hazardous reactions	Not applicable		
<u>Other information</u>			
Freezing Point		No information available	
Pour point	-20 °C		ASTM D 97

10. STABILITY AND REACTIVITY

<u>Reactivity</u>	None under normal processing.
<u>Chemical stability</u>	Stable under recommended storage conditions.
<u>Possibility of hazardous reactions</u>	None under normal processing.
<u>Conditions to Avoid</u>	Heat, flames and sparks. Take precautionary measures against static discharges. Heat (temperatures above flash point), sparks, ignition points, flames, static electricity. Strong oxidizing agents.
<u>Incompatible Materials</u>	Strong oxidizing agents.

Version GNAM



SDS # : 084009

TRANS. MDL NA 85W-140

Date of the previous version: 2015-09-21

Revision Date: 2015-10-13

Version 4.02

Hazardous Decomposition Products Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot.

11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Product Information Product does not present an acute toxicity hazard based on known or supplied information.

Information on likely routes of exposure

Principle Routes of Exposure Inhalation, Ingestion, Eye contact, Skin contact.

Numerical measures of toxicity

No information available

Information on toxicological effects

Symptoms	Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Itching.
Skin contact	Causes mild skin irritation. Prolonged contact may cause redness and irritation.
Eye contact	Causes eye irritation.
Inhalation	Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.
Ingestion	Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Serious eye damage/eye irritation	Irritating to eyes.
Sensitization	Not classified as a sensitizer.
Carcinogenicity	This product is not classified carcinogenic.

Mutagenicity	This product is not classified as mutagenic.
Reproductive toxicity	This product does not present any known or suspected reproductive hazards.
Aspiration Hazard	No information available.

12. ECOLOGICAL INFORMATION

Ecotoxicity May cause long lasting harmful effects to aquatic life
Harmful to aquatic life

Version GNAM



SDS # : 084009

TRANS. MDL NA 85W-140

Date of the previous version: 2015-09-21

Revision Date: 2015-10-13

Version 4.02

Acute aquatic toxicity - Product Information

No experimental data available

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates	Toxicity to microorganisms
1-Propene,2-Methyl-,sulfurized 68511-50-2		LC50 (96h) 250 - 500 mg/l (Pimephales promelas)	EC50(48h) > 1000 mg/l (Daphnia magna)	

Chronic aquatic toxicity - Product Information

No experimental data available

Chronic aquatic toxicity - Component Information

No information available

Effects on terrestrial organisms No experimental data available .**Persistence and degradability****General Information** No information available.**Bioaccumulative potential****Product Information** No information available.**logPow** No information available**Component Information** No information available.**Mobility****Soil** No information available**Other adverse effects****General Information** No information available**13. DISPOSAL CONSIDERATIONS****Waste treatment****Waste Disposal Methods** Dispose of in accordance with local regulations.

Version GNAM



SDS # : 084009

TRANS. MDL NA 85W-140

Date of the previous version: 2015-09-21

Revision Date: 2015-10-13

Version 4.02

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal.

This product contains one or more substances that are listed with the State of California as a hazardous waste.

14. TRANSPORT INFORMATION

<u>DOT</u>	Not regulated
<u>TDG</u>	Not regulated
<u>MEX</u>	Not regulated
<u>ICAO/IATA</u>	Not regulated
<u>IMDG/IMO</u>	Not regulated
<u>ADR/RID</u>	Not regulated
<u>ADN</u>	Not regulated

15. REGULATORY INFORMATION**International Inventories**

All the substances contained in this product are listed or exempted from listing in the following inventories:
U.S.A. (TSCA)

U.S. Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	no
Fire Hazard	no
Sudden Release of Pressure Hazard	no
Reactive Hazard	no

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Version GNAM



SDS # : 084009

TRANS. MDL NA 85W-140

Date of the previous version: 2015-09-21

Revision Date: 2015-10-13

Version 4.02

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations**California Proposition 65**

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

No information available

16. OTHER INFORMATION

NFPA	Health Hazard 1	Flammability 1	Instability 0	Physical and chemical hazards -
HMIS	Health Hazard 1	Flammability 1	Physical Hazard 0	Personal protection X

NFPA (National Fire Protection Association)

HMIS (Hazardous Material Information System)

Hazards are split into categories each with a 0 to 4 rating, 0 meaning no hazard and 4 meaning high hazard

Revision Date: 2015-10-13
Revision Note (M)SDS sections updated 2 3 4 15 16
Abbreviations, acronyms

Version GNAM



SDS # : 084009**TRANS. MDL NA 85W-140****Date of the previous version:** 2015-09-21**Revision Date:** 2015-10-13**Version** 4.02

Legend

Section 8

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH - National Institute for Occupational Safety and Health

TLV - Threshold Limit Values

PEL - Permissible Exposure Limits

IDLH - Immediately Dangerous to Life or Health concentrations

TWA - Time Weight Average

STEL - Short Term Exposure Limits

S* - Skin notation

TSCA - Toxic Substance Control Act

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the safety data sheet

Version GNAM