



## SAFETY DATA SHEET

According to the Hazard Communication Standard, 29 CFR 1910.1200

SDS # : 083168

### NEVASTANE AW 46

Date of the previous version: 2015-10-13

Revision Date: 2016-03-24

Version 1.02

#### 1. IDENTIFICATION

##### Product identifier

**Product name** NEVASTANE AW 46

##### Other means of identification

**Product Code(s)** 083168

**Number** JDH  
**Substance/mixture** Mixture

##### Recommended use of the chemical and restrictions on use

**Identified uses** Hydraulic oil. Lubricant for incidental food contact.

**Uses advised against** Do not use for any purpose other than the one for which it is intended

##### Details of the supplier of the safety data sheet

**Supplier Address** TOTAL Specialties USA Inc  
 5 North Stiles Street  
 Linden, New Jersey 07036  
 Tel: +1 800 323 3198  
 Fax: +1 908 862 6885

**Contact Point** Technical/ HSEQ

**E-mail Address** USRMLIN-info@total.com

##### Emergency telephone number

**Company Phone Number** +1 (908) 862-9300  
**Emergency telephone** +1 866 928 0789 (24h/24, 7d/7)  
 +1 215 207 0061 (24h/24, 7d/7)

#### 2. HAZARDS IDENTIFICATION

##### Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

##### Label elements

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Version GNAM



SDS # : 083168

## NEVASTANE AW 46

Date of the previous version: 2015-10-13

Revision Date: 2016-03-24

Version 1.02

### Unknown Acute Toxicity

No information available

### Hazards not otherwise classified (HNOC)

Not applicable

### Other information

#### Physical-Chemical Properties

Contaminated surfaces will be extremely slippery.

#### Environmental properties

Should not be released into the environment.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

### Mixture

Chemical Name	CAS-No	Weight %
White mineral oil (petroleum)	8042-47-5	20-25

*\* The exact percentage (concentration) of composition has been withheld as a trade secret*

## 4. FIRST AID MEASURES

### First aid measures for different exposure routes

#### General advice

IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.

#### Eye contact

Rinse immediately with plenty of water and seek medical advice.

#### Skin contact

Remove contaminated clothing and shoes. Wash off with soap and water. Wash contaminated clothing before reuse.

#### Inhalation

Move to fresh air. Inhalation of high concentrations of vapor or aerosols may cause irritation of the upper respiratory tract.

#### Ingestion

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.

### Most important symptoms/effects, acute and delayed

#### Skin contact

Not classified.

#### Eye contact

Not classified.

Version GNAM



SDS # : 083168

## NEVASTANE AW 46

Date of the previous version: 2015-10-13

Revision Date: 2016-03-24

Version 1.02

<b>Inhalation</b>	Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.
<b>Ingestion</b>	Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
<b>Symptoms</b>	Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

### Indication of immediate medical attention and special treatment needed, if necessary

**Notes to physician** Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

<b><u>Suitable Extinguishing Media</u></b>	Carbon dioxide (CO <sub>2</sub> ). ABC powder. Foam. Water spray or fog.
<b><u>Unsuitable Extinguishing Media</u></b>	Do not use a solid water stream as it may scatter and spread fire.
<b><u>Special Hazard</u></b>	Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration.
<b><u>Explosion Data</u></b>	
<b><u>Sensitivity to Mechanical Impact</u></b>	None.
<b><u>Sensitivity to Static Discharge</u></b>	None.
<b><u>Protective Equipment and Precautions for Firefighters</u></b>	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Evacuate non-essential personnel.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

<b>General Information</b>	Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.
<b>Other information</b>	See Section 12 for additional information.

### Environmental precautions

<b>General Information</b>	Do not allow material to contaminate ground water system. Try to prevent the material from entering drains or water courses. Local authorities should be advised if significant spillages cannot be contained.
----------------------------	--

### Methods and materials for containment and cleaning up

<b>Methods for cleaning up</b>	Dam up. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal.
--------------------------------	---

Version GNAM



SDS # : 083168

## NEVASTANE AW 46

Date of the previous version: 2015-10-13

Revision Date: 2016-03-24

Version 1.02

### 7. HANDLING AND STORAGE

#### Precautions for safe handling

<b>Advice on safe handling</b>	When using, do not eat, drink or smoke. For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing.
<b>Prevention of fire and explosion</b>	Take precautionary measures against static discharges. Ground/bond containers, tanks and transfer/receiving equipment.
<b>Hygiene measures</b>	Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.

#### Conditions for safe storage, including any incompatibilities

<b>Technical measures/Storage conditions</b>	Keep away from food, drink and animal feedingstuffs. Keep in a banded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Protect from frost, heat and sunlight. Protect from moisture.
--	--

<b>Materials to Avoid</b>	Strong oxidizing agents.
---------------------------	--------------------------

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

<b>Exposure limits</b>	Mineral oil mist: USA: OSHA (PEL) TWA 5 mg/m <sup>3</sup> , NIOSH (REL) TWA 5 mg/m <sup>3</sup> , STEL 10 mg/m <sup>3</sup> , ACGIH (TLV) TWA 5 mg/m <sup>3</sup> (highly refined).
------------------------	--

#### Exposure controls

<b>Engineering Measures</b>	Apply technical measures to comply with the occupational exposure limits.
-----------------------------	---

#### Individual protection measures, such as personal protective equipment

<b>General Information</b>	If the product is used in mixtures, it is recommended that you contact the appropriate protective equipment suppliers. These recommendations apply to the product as supplied.
----------------------------	--

Version GNAM



SDS # : 083168

## NEVASTANE AW 46

Date of the previous version: 2015-10-13

Revision Date: 2016-03-24

Version 1.02

<b>Eye/Face Protection</b>	If splashes are likely to occur, wear: Safety glasses with side-shields.
<b>Skin and body protection</b>	Wear suitable protective clothing. Protective shoes or boots.
<b>Hand Protection</b>	Hydrocarbon-proof gloves. Fluorinated rubber. Nitrile rubber. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
<b>Respiratory protection</b>	None required under normal usage. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
<b>Hygiene measures</b>	Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Physical and chemical properties

<b>Color</b>		amber	
<b>Physical State @20°C</b>		liquid	
<b>Odor</b>		Petroleum distillates	
<b>Odor Threshold</b>		No information available	
<b>Property</b>	<b>Values</b>	<b>Remarks</b>	<b>Method</b>
<b>pH</b>		Not applicable	
<b>Melting point/range</b>		No information available	
<b>Boiling point/boiling range</b>		Not applicable	
<b>Flash point</b>	<b>210 °C</b>		Cleveland Open Cup (COC)
	<b>410 °F</b>		ASTM D 92
			Cleveland Open Cup (COC).
			ASTM D 92.
<b>Evaporation rate</b>		No information available	
<b>Flammability Limits in Air</b>		No information available	
<b>upper</b>	-	No information available	
<b>Lower</b>	-	No information available	
<b>Vapor Pressure</b>		No information available	
<b>Vapor density</b>		No information available	
<b>Relative density</b>	0.846	@ 15 °C	ASTM D 1298

Version GNAM



SDS # : 083168

**NEVASTANE AW 46**

Date of the previous version: 2015-10-13

Revision Date: 2016-03-24

Version 1.02

Density	846 kg/m <sup>3</sup>	@ 15 °C	ASTM D 1298
Water solubility		Not applicable	
Solubility in other solvents		No information available	
logPow		No information available	
Autoignition temperature		Not applicable	
Decomposition temperature		No information available	
Viscosity, kinematic	46 mm <sup>2</sup> /s	@ 40 °C	ASTM D 445
Explosive properties	Not explosive		
Oxidizing Properties	Not applicable		
Possibility of hazardous reactions	Not applicable		
<u>Other information</u>			
Specific Gravity	0.846	@ 15 °C	ASTM D 1298
Freezing Point		No information available	
Pour point	-12 °C		ASTM D 97
Fire point	246 °C		ASTM D 92

**10. STABILITY AND REACTIVITY**

<u>Reactivity</u>	No information available.
<u>Chemical stability</u>	Stable under recommended storage conditions.
<u>Possibility of hazardous reactions</u>	None under normal processing.
<u>Conditions to Avoid</u>	Heat (temperatures above flash point), sparks, ignition points, flames, static electricity.
<u>Incompatible Materials</u>	Strong oxidizing agents.
<u>Hazardous Decomposition Products</u>	None under normal use.

**11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure

<b>Principle Routes of Exposure</b>	Inhalation, Ingestion, Eye contact, Skin contact.
<b>Symptoms</b>	Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
<b>Skin contact</b>	Not classified.
<b>Eye contact</b>	Not classified.
<b>Inhalation</b>	Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.
<b>Ingestion</b>	Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Version GNAM



SDS # : 083168

**NEVASTANE AW 46**

Date of the previous version: 2015-10-13

Revision Date: 2016-03-24

Version 1.02

**Delayed and immediate effects as well as chronic effects from short and long-term exposure****Acute toxicity - Product Information**

**Product Information** Product does not present an acute toxicity hazard based on known or supplied information.

**Oral**  
ATEmix (oral) 5052 mg/kg

**Dermal**  
ATEmix (dermal) 2426 mg/kg

**Inhalation**  
ATEmix (inhalation-dust/mist) 5.2 mg/l

**Acute toxicity - Component Information**

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
White mineral oil (petroleum) 8042-47-5	LD50 > 5000 mg/kg bw (rat)	LD50 > 2000 mg/kg bw (rabbit)	LC50 (4h) > 5000 mg/m <sup>3</sup> air (aerosol) (rat)

**Sensitization** Not classified as a sensitizer.  
**Carcinogenicity** This product is not classified carcinogenic.

**Mutagenicity** This product is not classified as mutagenic.  
**Reproductive toxicity** No information available.  
**Aspiration Hazard** Not classified.

**12. ECOLOGICAL INFORMATION****Ecotoxicity****Acute aquatic toxicity - Product Information**

No information available

**Acute aquatic toxicity - Component Information**

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates	Toxicity to microorganisms
White mineral oil (petroleum) 8042-47-5	EL50 (48h) > 100 mg (Pseudokirchnerella subcapitata - OECD 201)	LL50 (96h) > 100 mg/l (Oncorhynchus mykiss - OECD 203)	EL50 (48h) > 100 mg/l (Daphnia magna - OECD 202)	

**Chronic aquatic toxicity - Product Information**

No information available

Version GNAM



SDS # : 083168

**NEVASTANE AW 46**

Date of the previous version: 2015-10-13

Revision Date: 2016-03-24

Version 1.02

**Chronic aquatic toxicity - Component Information**

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
White mineral oil (petroleum) 8042-47-5		NOEL (21d) 10 mg/l (Daphnia magna - OECD 211)	NOEL (14/21d) > 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox)	

**Effects on terrestrial organisms** No information available.**Persistence and degradability****General Information** No information available.**Bioaccumulative potential****Product Information** No information available.**logPow** No information available**Component Information**

Chemical Name	log Pow
White mineral oil (petroleum) 8042-47-5	-

**Mobility****Soil** Given its physical and chemical characteristics, the product generally shows low soil mobility**Air** Loss by evaporation is limited**Water** Insoluble The product spreads on the surface of the water.**Other adverse effects****General Information** No information available**13. DISPOSAL CONSIDERATIONS****Waste treatment****Waste Disposal Methods** Dispose of in accordance with local regulations.**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

Version GNAM





SDS # : 083168

**NEVASTANE AW 46**

Date of the previous version: 2015-10-13

Revision Date: 2016-03-24

Version 1.02

**14. TRANSPORT INFORMATION**

<u>DOT</u>	Not regulated
<u>TDG</u>	Not regulated
<u>MEX</u>	Not regulated
<u>ICAO/IATA</u>	Not regulated
<u>IMDG/IMO</u>	Not regulated
<u>ADR/RID</u>	Not regulated
<u>ADN</u>	Not regulated

**15. REGULATORY INFORMATION**

International Inventories All the substances contained in this product are listed or exempted from listing in the following inventories:  
U.S.A. (TSCA)

**U.S. Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

**SARA 311/312 Hazard Categories**

Acute Health Hazard	no
Chronic Health Hazard	no
Fire Hazard	no
Sudden Release of Pressure Hazard	no
Reactive Hazard	no

**Clean Water Act**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

**Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)**

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

Version GNAM



SDS # : 083168

**NEVASTANE AW 46**

Date of the previous version: 2015-10-13

Revision Date: 2016-03-24

Version 1.02

**CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

**U.S. State Regulations****California Proposition 65**

This product does not contain any Proposition 65 chemicals.

**U.S. State Right-to-Know Regulations**

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois
Butylated Hydroxytoluene 128-37-0	X	X	X	

**16. OTHER INFORMATION**

<b>NFPA</b>	Health Hazard 0	Flammability 1	Instability 0	Physical and chemical hazards -
<b>HMIS</b>	Health Hazard 0	Flammability 1	Physical Hazard 0	Personal protection X

NFPA (National Fire Protection Association)

HMIS (Hazardous Material Information System)

Hazards are split into categories each with a 0 to 4 rating, 0 meaning no hazard and 4 meaning high hazard

Revision Date: 2016-03-24

Revision Note \*\*\* Indicates updated section

**Abbreviations, acronyms**

ACGIH = American Conference of Governmental Industrial Hygienists

bw = body weight

bw/day = body weight/day

EC x = Effect Concentration associated with x% response

GLP = Good Laboratory Practice

IARC = International Agency for Research of Cancer

LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one half) of a group of test animals

LD50 = 50% Lethal Dose - Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals

LL = Lethal Loading

NIOSH = National Institute of Occupational Safety and Health

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

NOEL = No Observed Effect Level

OECD = Organization for Economic Co-operation and Development

OSHA = Occupational Safety and Health Administration

UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material

Version GNAM



---

**SDS # :** 083168

## NEVASTANE AW 46

**Date of the previous version:** 2015-10-13**Revision Date:** 2016-03-24**Version** 1.02

---

**Legend**

Section 8

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH - National Institute for Occupational Safety and Health

TLV - Threshold Limit Values

PEL - Permissible Exposure Limits

IDHL - Immediately Dangerous to Life or Health concentrations

TWA - Time Weight Average

STEL - Short Term Exposure Limits

S\* - Skin notation

TSCA - Toxic Substance Control Act

---

**This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.**

**End of the Safety Data Sheet**

Version GNAM